


















SINGER MODEL 3333





















SEWING LIGHTWEIGHT FABRICS

Examples: Batiste, chiffon, organza, organdy, tricot, light weight jersey, silk, light weight linen







	STITCH	APPLICATION	NEEDLE TYPE NEEDLE SIZE	STITCH LENGTH	HELPFUL TIPS
<b>BASIC SEWING</b>					
		Sewing seams	Regular Point; Size 11/80	2	
		Topstitching	Regular Point; Size 11/80	2	
		Seam finishes	Regular Point; Size 11/80	2	Narrow the zig zag by turning the Stitch Selector dial to the right towards the narrow point of the zigzag.
		Seam finishes; Elastic insertion	Regular Point; Size 11/80	1	
		Blind hems	Regular Point; Size 11/80	2	Loosen upper thread tension slightly
		Shell tuck hems	Regular Point; Size 11/80	3	Best on lightweight knits like tricot
<b>STRETCH</b>					
		Blind hem on stretch knit fabric	Ball Point; Size 11/80	3	
		Seams for stretch knit fabrics	Ball Point; Size 11/80	S1 or S2	
		Seams for stretch knit fabrics	Ball Point; Size 11/80	S1 or S2	Use this stitch for a narrower seam allowance
		Seam & seam finish sewn at same time	Ball Point; Size 11/80	S1	Sew within seam allowance, then trim excess fabric next to raw edge
<b>DECORATIVE</b>					
		Decorative embellishment; Fabric edges	Regular Point; Size 11/80	1	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 11/80	3	
		Decorative embellishment	Regular Point; Size 11/80	S1	
		Join lace to fabric	Regular Point; Size 11/80	S2	
		Decorative embellishment	Regular Point; Size 11/80	S1	Use lightweight tear-away stabilizer under fabric to prevent puckering
<b>BUTTONHOLE</b>					
		Sewing buttonholes	Regular Point or Ball Point; Size 11/80		Use tear-away stabilizer under buttonhole; Sew on a test fabric first

**SEWING MEDIUM WEIGHT FABRICS**

Examples: cotton, wool, satin, chambray, rayon, linen, t-shirt knit


















	STITCH	APPLICATION	NEEDLE TYPE NEEDLE SIZE	STITCH LENGTH	HELPFUL TIPS
<b>BASIC SEWING</b>					
		Sewing seams	Regular Point; Size 14/90	2.5	
		Topstitching	Regular Point; Size 14/90	3	
		Sewing seam finishes	Regular Point; Size 14/90	2	Narrow the zig zag by turning the Stitch Selector dial to the right towards the narrow point of the zigzag.
		Elastic insertion; Repairing tears	Regular Point; Size 14/90	2	Reduce stitch length for repairing tears
		Blind hems	Regular Point; Size 14/90	2	Loosen upper thread tension slightly
		Shell tuck hems	Regular Point; Size 14/90	3	Best on medium weight stretch fabrics
<b>STRETCH</b>					
		Blind hem on stretch fabric	Ball Point; Size 14/90	2	
		Seams for stretch knit fabrics	Ball Point; Size 14/90	S1 or S2	
		Seams for stretch knit fabrics	Ball Point; Size 14/90	S1 or S2	
		Seams & seam finish for stretch knit fabrics	Ball Point; Size 14/90	S2	Sew within seam allowance, then trim excess fabric next to raw edge
		Seam & seam finish for stretch fabric	Ball Point; Size 14/90	S1	Sew within seam allowance, then trim excess fabric next to raw edge
		Seam & seam finish for stretch fabric	Ball Point; Size 14/90	S1	Sew within seam allowance, then trim excess fabric next to raw edge
<b>DECORATIVE</b>					
		Decorative embellishment; Fabric edges	Regular Point; Size 14/90	1	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S1	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S1 or S2	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S2	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S1	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	2	
		Decorative embellishment	Regular Point; Size 14/90	S1	
		Decorative embellishment	Regular Point; Size 14/90	S2	

**SEWING MEDIUM WEIGHT FABRICS CONTINUED**

	STITCH	APPLICATION	NEEDLE TYPE NEEDLE SIZE	STITCH LENGTH	HELPFUL TIPS
<b>DECORATIVE</b>					
		Decorative embellishment	Regular Point; Size 14/90	S2	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S2	
		Decorative embellishment	Regular Point; Size 14/90	S1	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 14/90	S2	Use lightweight tear-away stabilizer under fabric to prevent puckering
<b>BUTTONHOLE</b>					
		Sewing buttonholes	Regular Point or Ball Point; Size 14/90		Use tear-away stabilizer under buttonhole; Sew on a test fabric first

**SEWING HEAVY WEIGHT FABRICS**

Examples: Denim, canvas, duck, fleece, upholstery, corduroy, garment-weight leather or suede

	STITCH	APPLICATION	NEEDLE TYPE NEEDLE SIZE	STITCH LENGTH	HELPFUL TIPS
<b>BASIC SEWING</b>					
		Sewing seams	Regular Point; Size 16/100	3	
		Sewing seams or topstitching	Regular Point; Size 16/100	3	Use this stitch if you want a narrower seam allowance, or for topstitching.
		Seam finishes	Regular Point; Size 16/100	3	Sew within seam allowance, then trim excess fabric next to raw edge
		Elastic insertion; Repairing tears	Regular Point; Size 16/100	2	Reduce stitch length for repairing tears
<b>STRETCH</b>					
		Seams for stretch fabrics	Ball Point; Size 16/100	S1 or S2	
		Seams for stretch fabrics	Ball Point; Size 16/100	S1 or S2	Use this stitch if you want a narrower seam allowance.
		Seams and seam finishes for stretch fabrics	Ball Point; Size 16/100	S2	Sew within seam allowance, then trim excess fabric next to raw edge
		Seams and seam finishes for stretch fabrics	Ball Point; Size 16/100	S1	Sew within seam allowance, then trim excess fabric next to raw edge
<b>DECORATIVE</b>					
		Decorative embellishment	Regular Point; Size 16/100	1.5	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 16/100	S1	
		Decorative embellishment	Regular Point; Size 16/100	S1 or S2	Use lightweight tear-away stabilizer under fabric to prevent puckering
		Decorative embellishment	Regular Point; Size 16/100	S2	
		Decorative embellishment	Regular Point; Size 16/100	S1	
		Decorative embellishment	Regular Point; Size 16/100	S1	
		Decorative embellishment	Regular Point; Size 16/100	3	
<b>BUTTONHOLE</b>					
		Sewing buttonholes	Regular Point or Ball Point; Size 16/100		Use tear-away stabilizer under buttonhole; Sew on a test fabric first